

CASING WARRANTY NOW 6 YEARS AND 2 RETREADS

DURATURN



COMMERCIAL TIRES | 2020

DURATURN



TABLE OF CONTENTS

4	PRODUCT COMPARISON CHART
6	STEER TIRES
7	DRIVE TIRES
11	TRAILER TIRES
12	MIXED SERVICE TIRES
14	LIMITED WARRANTY

STEER



FEATURES

- 5-rib tread pattern including wide shoulders promotes durability and even wear in all-positions
- Enhanced siping and wide grooves allows for premium traction in both wet and dry conditions
- Full size complement from 19.5" to 24.5" rim diameters

COMPETITORS

- Bridgestone R294, R250F
- Goodyear G149 RSA, G159
- Hankook AH08, AH11, AH12
- Continental HSR, HSR-1
- Toyo M143
- Firestone FS507
- Kumho 955
- Michelin XZA1+



- 5-rib tread design with special tread compounds enhances even wear, traction in long haul steer axle positions
- Multiple sipes and decoupling grooves enhance tire wear and traction
- Durable casing design to promote retreading

- Bridgestone R287
- Goodyear G395 LHS
- Michelin XZA3
- Continental HSL
- Toyo M147, M137
- Firestone FS590+
- Kumho KLS01



- 5-rib tread pattern including wide shoulders promotes durability and even wear in all-positions
- Enhanced siping and wide grooves allows for premium traction in both wet and dry conditions

- Bridgestone R294, R250F
- Goodyear G149 RSA, G159
- Hankook AH08, AH11, AH12
- Continental HSR, HSR-1
- Toyo M143
- Firestone FS507
- Kumho 955
- Michelin XZA1+



- Strong all-position tread pattern designed for multiple on/off highway uses
- Heavy-duty casing construction for excellent performance in tough application

- Bridgestone R250
- Goodyear G149
- Hankook AH08, AH11
- Continental HSR
- Toyo M154, M137
- Firestone T559
- Kumho 983
- Michelin XZY3

DRIVE



FEATURES

- Innovative open shoulder tread design provides enhanced traction in multiple applications
- 25/32" original tread depth allows for excellent mileage
- Premium casing promotes stability and retreading

COMPETITORS

- Bridgestone M711, M725
- Goodyear G124, G182
- Hankook Z35A
- Continental HDL
- Toyo M610ZL
- Firestone FD663
- Kumho KRD03, 942
- Michelin XM+S4



- Closed shoulder design promotes long, even treadwear while maintaining excellent traction
- Extra deep 30/32" original tread depth suitable for all applications
- Durable casing allows for multiple retreads

- Bridgestone M726
- Goodyear G372
- Hankook DL01
- Continental HDL Eco Plus
- Toyo M608Z
- Firestone FD690+
- Kumho KLD01
- Michelin XDA3, XDA5



- Special compound for low rolling resistance and increased fuel efficiency
- Excellent footprint distributes weight-bearing forces evenly over a large area, ensuring uniform wear
- Wide tread width enhances wet grip

- Bridgestone M710 Ecopia
- Michelin XDA3/XD2
- Goodyear G572 HD Fuel Max
- Hankook DL11
- Toyo M657
- Firestone FD691
- Kumho KLD01e



- Innovative tread design and compounds promotes excellent traction and resist irregular wear
- Durable casing construction perfect for tough regional and urban use
- Deep original tread depth provides maximum tread life

- Bridgestone M724F
- Goodyear G362
- Hankook Z59
- Continental HDR
- Toyo M627
- Firestone FD690+
- Kumho KRD02
- Michelin XDA3, XDA5



- Innovative tread design and compounds promote excellent traction and resist irregular wear
- Deep original tread depth provides maximum tread life
- Durable casing construction perfect for tough regional and urban use

- Bridgestone M724F
- Goodyear G362
- Hankook Z59
- Continental HDR
- Toyo M627
- Firestone FD690+
- Kumho KRD02



- Optimized internal contour design significantly improves durability
- Open shoulder design with numerous lateral grooves dissipates heat
- Deep tread depth compound and wide tread footprint, deliver long mileage

- Bridgestone M770
- Michelin Multiway XD
- Continental Hybrid HD3
- Hankook Smartflex
- Toyo M610
- Firestone FD691
- Kumho KRD



- Aggressive tread design with siping provides excellent traction in all weather conditions
- Tread grooves are designed for outstanding cleaning ability in winter conditions
- Special tread compounds provide grip in extremely cold temperatures

- Michelin XDN2 All Weather
- Goodyear Ultra Grip RTD
- Continental HDW2
- Hankook DL 12 All Weather
- Toyo M920 All Season



- Extra deep 33/32" tread depth for on/off road applications
- Chip and cut resistant compounds offer long mileage and wear while reducing effect of cuts, snags and tears
- Aggressive tread offers excellent traction for severe off-highway use; no on-highway speed restriction

- Bridgestone M775
- Goodyear G177
- Hankook DM04
- Continental HDO

- Toyo M506Z
- Firestone T831
- Kumho 939
- Michelin XZL



- Chip and cut resistant compounds offer long mileage and wear while reducing effect of cuts, snags and tears
- Aggressive tread offers excellent traction for severe off-highway use; no on-highway speed restriction

- Bridgestone M711, M725
- Goodyear G362, G182
- Hankook Z35A
- Continental HDL

- Toyo M610ZL
- Firestone FD663
- Kumho KRD03
- Michelin XD4, XDE M+S



- Deep tread depth prolongs service life
- Specially designed tread pattern effectively protects against stone penetration
- Wide transverse grooves provide excellent traction and braking performance

- Bridgestone L355
- Michelin XZY
- Goodyear G288 MSA
- Hankook DM09

- Toyo M503
- Firestone T546
- Kumho D41



- Aggressive tread offers excellent traction in severe off-road conditions
- Chip, cut and abrasion resistant compounds contribute to long service life
- Sturdy casing delivers durable performance and retreadability

- Michelin X Works XDY
- Goodyear G622 RSD
- Bridgestone L320
- Hankook DM09

- Toyo M503
- Kumho KMD41


TRAILER



- Optimum tread design promotes even wear in free rolling and trailer axle positions
- Enhanced siping provides traction and fights irregular wear
- Durable casing design to promote retreading

- Bridgestone R195F
- Goodyear G316
- Hankook TL01
- Continental HTL

- Toyo M127
- Firestone FT455
- Michelin XT-1




- Special tread compounds allow for long life in trailer and all-position applications
- 5-rib design promotes traction and long life
- Casing design provides durability, toughness and enhances retreadability

- Bridgestone R195F
- Goodyear G316
- Hankook TL01
- Continental HTL

- Toyo M127
- Firestone FT455
- Michelin XT-1

MIXED SERVICE



- Strong all-position tread pattern designed for multiple on/off highway uses
- Heavy-duty casing construction for excellent performance in tough application

- Bridgestone M860, M850
- Goodyear G288
- Hankook AH10
- Continental MS520

- Toyo M320
- Firestone T819
- Kumho 973
- Michelin XZY3



- Wide all-position tread pattern designed for multiple on/off highway uses
- Heavy-duty casing construction for excellent performance in tough applications
- Available in tubeless and tube-type sizes

- Bridgestone M860, M850
- Goodyear G288
- Hankook AH10
- Continental MS520

- Toyo M320
- Firestone T819
- Kumho 973
- Michelin XZY3



- Tread pattern and heavy ply rating designed for multiple uses
- Extra wide 5-rib design excellent for free rolling applications
- Durable casing provides long original tread life and promotes multiple retreads

- Bridgestone M844F
- Goodyear G286
- Hankook AM02
- Continental HTC

- Toyo M320Z
- Firestone T839
- Kumho 943W
- Michelin XZUS



- Aggressive multi-purpose tread design ideal for on/off highway applications
- Large tread elements offer improved handling and excellent traction
- Heavy-duty belt package and undertread offer increased durability, uniform wear and stability

- Bridgestone M844F
- Goodyear G286
- Hankook AM02
- Continental HTC
- Toyo M320Z

- Firestone T839
- Kumho 943W
- Michelin XZY3, XZUS



- Abrasion resistant compound, combined with wide tread footprint, contributes to long tread wear
- Innovative sipe design helps dissipate heat and reduce rolling noise
- Four zigzag tread pattern provides excellent handling and overall control

- Bridgestone R238
- Michelin X Line Energy Z
- Toyo M122
- Hankook A110+ e-cube max

STEER

PREMIUM STEER/ALL-POSITION TIRE

- 5-rib tread pattern including wide shoulders promotes durability and even wear in all-positions
- Enhanced siping and wide grooves allows for premium traction in both wet and dry conditions
- Full size complement from 19.5" to 24.5" rim diameters

DA20 (Y201)

DURATURN #	DYNACARGO #	TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER	SECTION WIDTH	MAX LOAD SINGLE/DUAL	INFLATION PRESSURE	SPEED SYMBOL	LOAD INDEX	WEIGHT (LB)
1203281255	1213811255	*11R22.5	14	G	8.25	19	41.4	11	6175/5840	105	M	144/142	119
1203281256	1213811256	*11R22.5	16	H	8.25	19	41.4	11	6610/6005	120	M	146/143	119
1203281455	1213811455	*11R24.5	14	G	8.25	19	43.3	11	6610/6005	105	L	146/143	129
1203281456	1213811456	*11R24.5	16	H	8.25	19	43.3	11	7160/6610	120	L	149/146	129
1203289255	1213819255	*295/75R22.5	14	G	9.00	19	40.6	11.7	6175/5675	110	M	144/141	109
1203288455	1213818455	*285/75R24.5	14	G	8.25	19	41.5	11.1	6175/5675	110	M	144/141	117
1203282258	1213282258	12R22.5	18	J	9.00	21	42.7	11.8	7830/7160	135	L	152/149	138
1203282275	1213282275	225/70R19.5	12	F	6.75	16	31.9	8.9	3640/3415	95	M	125/123	67
1203282276	1213282276	225/70R19.5	14	G	6.75	16	31.9	8.9	3970/3750	110	M	128/126	67
1203284796	1213284796	245/70R19.5	16	H	7.50	16	33	9.8	4805/4540	120	L	135/133	76
1203286796	1213286796	265/70R19.5	16	H	7.50	16	34.3	10	6005/5675	123	K	143/141	82
1203289254	1213289254	295/60R22.5	18	J	9.00	20	36.5	11.5	7390/6780	130	K	150/147	105
1203289258	1213289258	295/80R22.5	18	J	9.00	19	41.2	11.7	7830/7160	130	M	152/149	126
1203283157	1213283157	315/70R22.5	18	J	9.00	18	40	12.3	7610/6940	120	M	151/148	118
1203281257	1213281257	315/80R22.5	18	J	9.00	20	42.5	12.2	8820/7830	120	M	156/152	138
1203281258	1213281258	315/80R22.5	20	J	9.00	20	42.36	12.3	9090/8270	120	L	157/154	138

STEER

PREMIUM DECOUPLING GROOVE STEER TIRE

- 5-rib tread with special tread compounds enhances even wear, traction in long haul steer axle positions
- Multiple sipes and decoupling grooves enhance tire wear and traction
- Durable casing design to promote retreading

DS28 (Y208)

DURATURN #	DYNACARGO #	TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER	SECTION WIDTH	MAX LOAD SINGLE/DUAL	INFLATION PRESSURE	SPEED SYMBOL	LOAD INDEX	WEIGHT (LB)
1203291255	1213881255	*11R22.5	14	G	8.25	19	41.4	11	6175/5840	105	M	144/142	118
1203291256	1213881256	*11R22.5	16	H	8.25	19	41.4	11	6610/6005	120	M	146/143	118
1203291455	1213881455	*11R24.5	14	G	8.25	19	43.3	11	6610/6005	105	L	146/143	128
1203291456	1213881456	*11R24.5	16	H	8.25	19	43.3	11	7160/6610	120	L	149/146	128
1203298455	1213888455	*285/75R24.5	14	G	8.25	19	41.5	11.1	6175/5675	110	M	144/141	116
1203299255	1213889255	*295/75R22.5	14	G	9	19	40.6	11.7	6175/5675	110	M	144/141	106

STEER

PREMIUM ON/OFF HIGHWAY MIXED SERVICE ALL-POSITION TIRE

- Strong all-position tread pattern designed for multiple on/off highway uses
- Heavy-duty casing construction for excellent performance in tough application

Y606 (Y606)

DURATURN #	DYNACARGO #	TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER	SECTION WIDTH	MAX LOAD SINGLE/DUAL	INFLATION PRESSURE	SPEED SYMBOL	LOAD INDEX	WEIGHT (LB)
1203667165	1213667165	7.00R16	14	G	5.50F	17	30.5	7.9	2910/2600	112/112	M	118/114	56

STEER

PREMIUM STEER/ALL-POSITION TIRE

- 5-rib tread pattern including wide shoulders promotes durability and even wear in all-positions
- Enhanced siping and wide grooves allows for premium traction in both wet and dry conditions

Y207 (Y207)

DURATURN #	DYNACARGO #	TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER	SECTION WIDTH	MAX LOAD SINGLE/DUAL	INFLATION PRESSURE	SPEED SYMBOL	LOAD INDEX	WEIGHT (LB)
1203372258	1213372258	12R22.5	18	J	9.00	20	42.7	11.8	7830/7160	135/135	L	152/149	139

DRIVE

WINTER

- Aggressive tread design with siping provides excellent traction in all weather conditions
- Tread grooves are designed for outstanding cleaning ability in winter conditions
- Special tread compounds provide grip in extremely cold temperatures

D70 WINTER (Y701)

DURATURN #	DYNACARGO #	TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER	SECTION WIDTH	MAX LOAD SINGLE/DUAL	INFLATION PRESSURE	SPEED SYMBOL	LOAD INDEX	WEIGHT (LB)
1203711256	1213711256	11R22.5	16	H	8.25	26	41.9	11.0	6610/6005	120	M	146/143	128
1203711456	1213711456	11R24.5	16	H	8.25	26	43.9	11.0	7160/6610	120	L	149/146	137



- Innovative open shoulder tread design provides enhanced traction in multiple applications
- 25/32" original tread depth allows for excellent mileage
- Premium casing promotes stability and retreading

DD10 (Y101)

DURATURN #	DYNACARGO #	TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER	SECTION WIDTH	MAX LOAD SINGLE/DUAL	INFLATION PRESSURE	SPEED SYMBOL	LOAD INDEX	WEIGHT (LB)
1203411255	1213411255	11R22.5	14	H	8.25	25	41.7	11	6175/5840	105	M	144/142	124
1203411256	1213411256	11R22.5	16	G	8.25	25	41.7	11	6610/6005	120	M	146/143	124
1203411455	1213411455	11R24.5	14	G	8.25	25	43.7	11	6610/6005	120	L	146/143	135
1203411456	1213411456	11R24.5	16	H	8.25	25	43.7	11	7160/6610	105	L	149/146	135
1203412258	1213412258	12R22.5	18	J	9	28	43	11.9	7830/7160	120	L	152/149	149
1203419255	1213419255	295/75R22.5	14	G	9	25	40.9	11.7	6175/5675	110	L	144/141	117
1203419258	1213419258	295/80R22.5	18	J	9	28	41.8	11.7	7830/7160	130	M	152/149	133
1203411257	1213411257	315/80R22.5	18	J	9	28	43.2	12.5	8820/7830	120	L	156/152	144
1203418455	1213418455	285/75R24.5	14	G	8.25	19	41.9	11.1	6175/5675	110	L	144/141	123



- Closed shoulder design promotes long, even treadwear while maintaining excellent traction
- Extra deep 30/32" original tread depth suitable for all applications
- Durable casing allows for multiple retreads

DD13 (Y103)

DURATURN #	DYNACARGO #	TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER	SECTION WIDTH	MAX LOAD SINGLE/DUAL	INFLATION PRESSURE	SPEED SYMBOL	LOAD INDEX	WEIGHT (LB)
1203481255	1213481255	11R22.5	14	G	8.25	30	41.9	11	6175/5840	105	L	144/142	124
1203481256	1213481256	11R22.5	16	H	8.25	30	41.9	11	6610/6005	120	L	146/143	124
1203481455	1213481455	11R24.5	14	G	8.25	30	43.9	11	6610/6005	105	L	146/143	139
1203481456	1213481456	11R24.5	16	H	8.25	30	43.9	11	7160/6610	120	L	149/146	139
1203489255	1213489255	295/75R22.5	14	G	9	30	40.2	11.7	6175/5675	110	L	144/141	115
1203488455	1213488455	285/75R24.5	14	G	8.25	30	41.6	11.1	6175/5675	110	L	144/141	125
1203483157	1213483157	315/70R22.5	18	J	9	28	41	12.3	7610/6940	120	M	151/148	N/A
1203489253	1213489253	295/60R22.5	18	J	9	28	36.5	11.5	7390/6780	130	L	150/147	N/A

DD13 (Y103) FE

- Special compound for low rolling resistance and increased fuel efficiency

DURATURN #	DYNACARGO #	TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER	SECTION WIDTH	MAX LOAD SINGLE/DUAL	INFLATION PRESSURE	SPEED SYMBOL	LOAD INDEX	WEIGHT (LB)
1203831255	1213831255	11R22.5	14	G	8.25	27	41.9	11	6175/5840	105	L	144/142	124
1203831256	1213831256	11R22.5	16	H	8.25	27	41.9	11	6610/6005	120	L	146/143	124
1203831455	1213831455	11R24.5	14	G	8.25	27	43.9	11	6610/6005	105	L	146/143	139
1203831456	1213831456	11R24.5	16	H	8.25	27	43.9	11	7160/6610	120	L	149/146	139
1203839255	1213839255	295/75R22.5	14	G	9	30	40.2	11.7	6175/5675	110	L	144/141	115
1203838455	1213838455	285/75R24.5	14	G	8.25	30	41.6	11.1	6175/5675	110	L	144/141	125
1203483157	1213483157	315/70R22.5	18	J	9	28	41	12.3	7610/6940	120	M	151/148	N/A
1203489253	1213489253	295/60R22.5	18	J	9	28	36.5	11.5	7390/6780	130	L	150/147	N/A



- Innovative tread design and compounds promotes excellent traction and resist irregular wear
- Durable casing construction perfect for tough regional and urban use
- Deep original tread depth provides maximum tread life

DD15 (Y105)

DURATURN #	DYNACARGO #	TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER	SECTION WIDTH	MAX LOAD SINGLE/DUAL	INFLATION PRESSURE	SPEED SYMBOL	LOAD INDEX	WEIGHT (LB)
1204901256	1214901256	11R22.5	16	H	8.25	25	41.9	11	6610/6005	120	L	146/143	127
1204902258	1214902258	12R22.5	18	J	9	25	43.2	11.9	7830/7610	135	L	152/149	149
1204903227	1214903227	13R22.5	18	J	9.75	26	44.7	12.6	8270/7610	120	K	154/151	170
1204901257	1214901257	315/80R22.5	18	J	9	25	42.5	12.2	8270/7610	120	M	154/151	145
1204903157	1214903157	315/70R22.5	18	J	9	24	40.16	12.3	7610/6940	120	M	151/148	144
1204909254	1214909254	295/60R22.5	18	J	8.5	20	48	12.2	7390/6780	130	L	150/147	150



- Innovative tread design and compounds promote excellent traction and resist irregular wear
- Deep original tread depth provides maximum tread life
- Durable casing construction perfect for tough regional and urban use

DD51 (Y501)

DURATURN #	DYNACARGO #	TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER	SECTION WIDTH	MAX LOAD SINGLE/DUAL	INFLATION PRESSURE	SPEED SYMBOL	LOAD INDEX	WEIGHT (LB)
1203612796	1213612796	225/70R19.5	14	G	6.75	19	32.6	8.8	3970/3750	110	L	128/126	69.97
1203614795	1213614795	245/70R19.5	14	G	7.50	19	33.5	9.6	4540/4300	110	L	133/131	79.19
1203616796	1213616796	265/70R19.5	16	H	7.50	22	34.6	10	6005/5675	123	M	143/141	89.2
1203616797	1213616797	265/70R19.5	18	J	7.50	22	34.6	10	6175/5840	125	L	144/142	86




- Optimized internal contour design significantly improves durability
- Open shoulder design with numerous lateral grooves dissipates heat
- Deep tread depth compound and wide tread footprint, deliver long mileage

DD25 (Y115)

DURATURN #	DYNACARGO #	TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER	SECTION WIDTH	MAX LOAD SINGLE/DUAL	INFLATION PRESSURE	SPEED SYMBOL	LOAD INDEX	WEIGHT (LB)
1204909254	1214959254	295/60R22.5	18		9	24	36.46	11.5	7390/6780		K	150/147	110
1204903157	1214953157	315/70R22.5	18		9	24	40.16	12.3	7610/6940		M	151/148	131

DRIVE




PREMIUM EXTRA DEEP ON/OFF HIGHWAY SEVERE SERVICE DRIVE-POSITION TIRE

- Extra deep 33/32" tread depth for on/off road applications
- Chip and cut resistant compounds offer long mileage and wear while reducing effect of cuts, snags and tears
- Aggressive tread offers excellent traction for severe off-highway use; no on-highway speed restriction

DD11 (Y131)

DURATURN #	DYNACARGO #	TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER	SECTION WIDTH	MAX LOAD SINGLE/DUAL	INFLATION PRESSURE	SPEED SYMBOL	LOAD INDEX	WEIGHT (LB)
1203491256	1213491256	11R22.5	16	H	8.25	33	43	11.1	6610/6005	120	G	146/143G	133
1203491456	1213491456	11R24.5	16	H	8.25	33	44	11.1	7160/6610	120	G	149/146G	144

DRIVE




- Deep tread depth prolongs service life
- Specially designed tread pattern effectively protects against stone penetration
- Wide transverse grooves provide excellent traction and braking performance

DM56 (Y516)

DURATURN #	DYNACARGO #	TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER	SECTION WIDTH	MAX LOAD SINGLE/DUAL	INFLATION PRESSURE	SPEED SYMBOL	LOAD INDEX	WEIGHT (LB)
1203502250		12.00R24	20		8.5	25	48.74	12.4	9920/9090		K	160/157	190

DRIVE




- Chip and cut resistant compounds offer long mileage and wear while reducing effect of cuts, snags and tears
- Aggressive tread offers excellent traction for severe off-highway use; no on-highway speed restriction

Y866 (Y866)

DURATURN #	DYNACARGO #	TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER	SECTION WIDTH	MAX LOAD SINGLE/DUAL	INFLATION PRESSURE	SPEED SYMBOL	LOAD INDEX	WEIGHT (LB)
1203731028	1213731028	10.00R20	18	J	7.5	24	41.5	10.9	7160/6610	135/135	K	149/146	138

DRIVE




- Aggressive tread offers excellent traction in severe off-road conditions
- Chip, cut and abrasion resistant compounds contribute to long service life
- Sturdy casing delivers durable performance and retreadability

D50

DURATURN #	DYNACARGO #	TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER	SECTION WIDTH	MAX LOAD SINGLE/DUAL	INFLATION PRESSURE	SPEED SYMBOL	LOAD INDEX	WEIGHT (LB)
1205291256	1215291256	11R22.5	16	H	8.25	27	41.9	11	6610/6005	120	L	146/143	129
1205291456	1215291456	11R24.5	16	H	8.25	27	43.9	11	7160/6610	120	M	149/146	138
1205292258	1215292258	12R22.5	18	J	9.00	27	42.7	11.8	7830/7160	135	L	152/149	156
1205299258	1215299258	295/80R22.5	18	J	9.00	23.5	41.7	11.7	7830/7160	130	L	152/149	141
1205291258	1215291258	315/80R22.5	20	J	9.00	24.5	42.6	10	9090/8270	130	G	157/154	156

TRAILER




PREMIUM SHALLOW DEPTH TRAILER-POSITION TIRE

- Optimum tread design promotes even wear in free rolling and trailer axle positions
- Enhanced siping provides traction and fights irregular wear
- Durable casing design to promote retreading

DT22 (Y202)

DURATURN #	DYNACARGO #	TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER	SECTION WIDTH	MAX LOAD SINGLE/DUAL	INFLATION PRESSURE	SPEED SYMBOL	LOAD INDEX	WEIGHT (LB)
1203381255	1213821255	*11R22.5	14	G	8.25	12	41	11.0	6175/5840	105	M	144/142	107.45
1203381455	1213821455	*11R24.5	14	G	8.25	12	42.9	11.0	6610/6005	105	L	146/143	116.49
1203389255	1213829255	*295/75R22.5	14	G	9.00	12	40.2	11.7	6175/5675	110	M	144/141	100.16
1203388455	1213828455	*285/75R24.5	14	G	8.25	12	41.1	11.1	6175/5675	110	L	144/141	107.37

TRAILER



PREMIUM LOW PROFILE MULTI-USE TRAILER-POSITION TIRE

- Special tread compounds allow for long life in trailer and all-position applications
- 5-rib design promotes traction and long life
- Casing design provides durability, toughness and enhances retreadability

DT23 (Y203)

DURATURN #	DYNACARGO #	TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER	SECTION WIDTH	MAX LOAD SINGLE/DUAL	INFLATION PRESSURE	SPEED SYMBOL	LOAD INDEX	WEIGHT (LB)
1203397565	1213397565	7.50R16 LT	14	G	6	16	31.7	8.3	3305/2910	112	M	122/118	63
1203392964	1213392964	ST225/90R16	10		6.00	16	31.8	8.6	3520/3080		M	124/120	63
1203393855	1213393855	ST235/85R16	14		6.50	12	31.7	9.3	4080/3640		L	129/125	59
1203391784	1213391784	8R17.5	12		6.00	16	30.9	8.2	3307/3087		J	122/120	57
1203391706	1213391706	10R17.5	16		7.50	16	33.8	10	6005/5675		J	143/141	80
1203391776	1213391776	215/75R17.5	16	H	6.00	16	30.2	8.3	4805/4540	125	L	135/133	60
1203396795	1213396795	235/75R17.5	16	H	6.75	16	31.4	9.2	6010/5680	125	L	143/141	67
1203395726	1213395726	255/70R22.5	16	H	7.50	13	36.6	10	5510/5070	120	N	140/137	84
1203397726	1213397726	275/70R22.5	16	H	8.25	16	37.7	10.9	6940/6395	130	M	148/145	103
1203397165	1213397165	7.00R16 LT	14	G	5.50F	15	30.5	7.9	2910/2600	112	M	118/114	56

11

MIXED SERVICE

PREMIUM ON/OFF HIGHWAY ALL-POSITION TIRE

- Wide all-position tread pattern designed for multiple on/off highway uses
- Heavy-duty casing construction for excellent performance in tough applications
- Available in tubeless and tube-type sizes

DM60 (Y601)

DURATURN #	DYNACARGO #	TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER	SECTION WIDTH	MAX LOAD SINGLE/DUAL	INFLATION PRESSURE	SPEED SYMBOL	LOAD INDEX	WEIGHT (LB)
1203998206	1213998206	8.25R20	16		6.5	20	38.3	9.29	5355/5070		K	139/137	94
1203999206	1213999206	9.00R20	16	H	7.00	20	40.1	10.2	6170/5840	130	K	144/142	105
1203991028	1213991028	10.00R20	18	H	7.50	21	41.5	10.9	6610/6010	120	K	146/143	120
1203991208	1213991208	11.00R20	18	J	8.00	21	42.7	11.5	7830/7160	135	K	152/149	138
1203991408	1213991408	12.00R20	18	J	8.50	22	44.3	12.4	8270/7610	120	K	154/151	155
1203992248	1213992248	12.00R24	20	L	8.50	20	48	12.2	9920/9090	130	K	160/157	174
1203991256	1213991256	11R22.5	16	H	8.25	19	41.4	11.0	6610/6005	120	M	146/143	120
1203992258	1213992258	12R22.5	18	J	9.00	21	42.7	11.8	7830/7160	135	L	152/149	141
1203991456	1213991456	11R24.5	16	H	8.25	19	43.3	11.0	7160/6610	120	L	149/146	131
1203991257	1213991257	315/80R22.5	18	J	9.00	20	42.5	12.2	8820/7830	120	M	156/152	138
1203991259	1213991259	315/80R22.5	22	M	9.00	20	42.5	12.2	100000/9090	130	65 MPH	160/157	152

MIXED SERVICE

- Strong all-position tread pattern designed for multiple on/off highway uses
- Heavy-duty casing construction for excellent performance in tough application

DA25 (Y205)

DURATURN #	DYNACARGO #	TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER	SECTION WIDTH	MAX LOAD SINGLE/DUAL	INFLATION PRESSURE	SPEED SYMBOL	LOAD INDEX	WEIGHT (LB)
1203271256	1213271256	11R22.5	16	H	8.25	22	41.4	11.0	6610/6005	120	L	146/143	122
1203272258	1213272258	12R22.5	18	J	9.00	22	42.7	11.8	7830/7160	135	L	152/149	145
1203273227	1213273227	13R22.5	18	J	9.75	22	42.4	12.6	8270/7610	120	K	154/151	169
1203271257	1213271257	315/80R22.5	18	J	9.00	22	42.5	12.2	8820/7830	120	M	154/151	141
1203271258	1213271258	315/80R22.5	20	J	9.00	23	42.3	12.2	9090/8270		L	157/154	141
1203272248	1213272248	12.00R24	20	L	8.50	20	48	12.2	9920/9090	130	K	160/157	176

MIXED SERVICE

ULTRA PREMIUM WIDE BASE MIXED SERVICE ALL-POSITION TIRE

- Aggressive multi-purpose tread design ideal for on/off highway applications
- Large tread elements offer improved handling and excellent traction
- Heavy-duty belt package and undertread offer increased durability, uniform wear and stability

DM63 (Y631)

DURATURN #	DYNACARGO #	TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER	SECTION WIDTH	MAX LOAD SINGLE/DUAL	INFLATION PRESSURE	SPEED SYMBOL	LOAD INDEX	WEIGHT (LB)
1206318258	1216318258	385/65R22.5	20	L	11.75	22	42.2	14.8	9920/NA	130	K/L	160/158	180
1206312258	1216312258	425/65R22.5	20	L	13.00	22	44.6	16.3	11400/NA	120	K	165	195

MIXED SERVICE

PREMIUM WIDE BASE ALL-POSITION TIRE

- Tread pattern and heavy ply rating designed for multiple uses
- Extra wide 5-rib design excellent for free rolling applications
- Durable casing provides long original tread life and promotes multiple retreads

DT63 (Y603)

DURATURN #	DYNACARGO #	TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER	SECTION WIDTH	MAX LOAD SINGLE/DUAL	INFLATION PRESSURE	SPEED SYMBOL	LOAD INDEX	WEIGHT (LB)
1203648258	1213648258	385/65R22.5	20	L	11.75	20	42	14.8	9920/NA	130	K/L	160/158	154
1203643557	1213643557	435/50R19.5	18	J	14.00	17.5	37	17.2	8820/NA	123	L	156/NA	NA
1203648257	1213648257	385/55R22.5	20	L	12.25	20	42	14.8	9370/MA	123	L	158/NA	146

MIXED SERVICE

PREMIUM ON/OFF HIGHWAY SEVERE SERVICE DRIVE-POSITION TIRE

- Abrasion resistant compound, combined with wide tread footprint, contributes to long tread wear
- Innovative sipe design helps dissipate heat and reduce rolling noise
- Four zigzag tread pattern provides excellent handling and overall control

DA21 (Y211)

DURATURN #	DYNACARGO #	TIRE SIZE	PLY RATING	LOAD RANGE	RIM (INCH)	TREAD DEPTH (32NDS)	OVERALL DIAMETER	SECTION WIDTH	MAX LOAD SINGLE/DUAL	INFLATION PRESSURE	SPEED SYMBOL	LOAD INDEX	WEIGHT (LB)
1203219212	1213219212	9R22.5	12		6.75	18	38.35	9.02	4540/4300		M	133/131	91
1203219214	1213219214	9R22.5	14		6.75	18	38.35	9.02	4938/4674		L	136/134	91
1203210225	1213210225	10R22.5	14		7.5	19	40.12	10	5675/5355		L	141/139	106
1203210226	1213210226	10R22.5	16		7.5	19	40.12	10	6175/5840		M	144/142	106



DURATURN RADIAL TBR TIRE LIMITED WARRANTY

LIMITED WARRANTY

Duraturn Radial TBR (Truck and Bus Radial) Tire Limited Manufacturers Warranty November 1, 2018.

TO OBTAIN AN ADJUSTMENT

- a. You must present the tire to be adjusted to a current Duraturn Commercial Truck Tire Dealer. (Please consult your telephone directory for locations or visit our dealer locator on our website at www.duraturntires.com). Tires replaced on an adjustment basis become the property of Duraturn.
- b. You must pay for taxes, fees or any additional services you order at the time of adjustment.
- c. No claim will be recognized unless submitted on a Duraturn claim form (supplied by the Duraturn Commercial Truck Tire Dealer), completely filled out and signed by you, the owner of the tire presented for adjustment, or your authorized agent.

FOR SERVICE ASSISTANCE OR INFORMATION

1. First contact the nearest Authorized Duraturn Commercial Truck Tire Dealer.
2. If additional assistance is required:
 - Visit our website at www.duraturntires.com.
 - E-mail The Duraturn Customer Relations Department at info@duraturntires.com or
 - Write to
Duraturn Customer Assistance
Service Department
406 E. Huntington Drive, Suite 200
Monrovia, CA 91016

WHO IS ELIGIBLE FOR WARRANTY COVERAGE

You are eligible for the benefits of this warranty if you meet all the following criteria:

- You are the owner or authorized agent of the owner of new Duraturn Truck Bus Radial (TBR) tires.
- Your tires bear Department of Transportation (DOT) prescribed tire identification numbers and are not branded “NA” (Not Adjustable).
- Your Duraturn truck tires have been used only on the vehicle on which they were originally installed according to the vehicle manufacturers or Duraturn recommendations.

Your tires were purchased on or after January 1, 2014.

WHAT IS COVERED UNDER THIS WARRANTY AND FOR HOW LONG

PRORATED TIRE REPLACEMENT

Duraturn truck tires covered by this warranty that become unserviceable due to a defect in workmanship or material during the life of the original usable tread (down to 2/32” remaining usable tread), will be reimbursed to the owner on a prorated basis. You pay only for the mounting, balancing, taxes and fees.

HOW TO CALCULATE THE PRORATED AMOUNT

The replacement price will be calculated by multiplying the current Duraturn “predetermined price for adjustment” or current advertised selling price at the adjustment location (whichever is lower) by the percentage of usable original tread that has been worn off at the time of adjustment. You pay for mounting, balancing, and amount equal to the full current Federal Excise Tax and any other applicable taxes and fees for the comparable new Duraturn replacement tire.

PRORATED REIMBURSEMENT EXAMPLE

If your disabled tire had an original 16/32” of usable tread depth and is worn to 8/32” of usable tread remaining you have used 50% and therefore must pay 50% of the predetermined price for adjustment or advertised selling price of a comparable tire, plus an amount equal to the full current Federal Excise Tax applicable to the comparable new replacement tire at the time of adjustment. If the price of the comparable tire is \$400.00, the cost to you would be \$200.00 plus Federal Excise Tax, mounting, balancing and any other applicable taxes.

DEFINITION OF A COMPARABLE TIRE

A “comparable” new Duraturn tire may either be the same line of tire or, in the event that the same tire is not available, a tire of the same basic construction and quality with a different sidewall or tread configuration. If a higher priced tire is accepted as replacement, the difference in price will be at an additional charge to you.

Any replacement tire provided pursuant to this warranty will be covered by the Duraturn warranty in effect at the time of replacement.

WHAT THIS WARRANTY DOES NOT COVER

IRREGULAR WEAR OR TIRE DAMAGE DUE TO:

- Road hazards (including punctures, cuts, snags, impact breaks, etc.)
- Wreck, collision, or fire.
- Improper inflation, overloading, high speed spinup, misapplication, misuse, negligence, racing, chain damage, or improper mounting or demounting.
- Mechanical condition of the vehicle.
- Ride disturbance after the first 2/32” treadwear or due to damaged wheels or any vehicle condition.
- Any tire intentionally altered after leaving a factory producing Duraturn tires to change its appearance (example: white inlay on a black tire).
- Tires with weather cracking which were purchased more than five (5) years prior to presentation for adjustment. If you have no proof of purchase date, tires manufactured five (5) or more years prior to presentation are not covered.
- This limited warranty is applicable only in the United States, Canada & Mexico, and any tire used or equipped on a vehicle registered or operated outside the U.S., Canada & Mexico are not covered by this warranty.
- Tire branded or marked “Non-Adjustable” (N/A) or “Blemished” (Blem), or previously adjusted.

FAILURE, DAMAGE, OR IRREGULAR WEAR DUE TO:

- Accident or vandalism, improper misalignment, wheel imbalance, faulty shocks or brakes;
- Mechanical condition of vehicle, including misalignment, wheel imbalance, faulty shocks or brakes;
- Misapplication of tire, use of improper inner tube;
- Alteration of the tire or addition of alien material or transfer from one vehicle to another; and
- Radial truck tire failed due to faulty retreading or material.
- Cost of mounting and balancing service except as noted above.
- Loss of time or use, inconvenience, or any incidental or consequential damages.
- Material added to a tire after leaving a factory producing Duraturn tires: (example: tire fillers, sealants, or balancing substances). If the added material is the cause of the tire being removed from service, the tire will not be adjusted.
- Loss of time, inconvenience, loss of use of vehicle, incidental or consequential damage.

YOUR LEGAL RIGHTS

Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusions may not apply to you.

No representative or dealer has authority to make any representation, promise, or agreement on behalf of Duraturn, except as stated herein.

Any tire, no matter how well constructed, may fail in service or otherwise become unserviceable due to conditions beyond the control of the manufacturer. Under no circumstances is this warranty a representation that a tire failure cannot occur.

This warranty gives you specific legal rights, and you may also have other rights that vary from state to state.

This limited warranty is applicable only in the United States, Canada & Mexico.

END OF WARRANTY

A tire has delivered its full original tread life and the new tire coverage of this warranty ends when the treadwear indicators become visible, or five (5) years from the date of original tire manufacture or new tire purchase date. (Without proof of purchase, date of manufacture will be used to determine age.) Casings may continue to be warranted beyond the new tire coverage. Please refer to the Radial Casing Provision for warranty details on casings.

THE DURATURN RADIAL CASING’S PROVISION

Truck Tire Casings will be warranted against defects in workmanship or material through a period of six (6) years from the date of the casings DOT serial number or proof of purchase, if available, whichever comes first. If a Duraturn truck tire dealer examines a casing and finds such a defect, Duraturn will reimburse the owner for the casing according to the following schedule:

DURATURN CASING VALUES	CASING VALUES (DURATURN)
TUBELESS	
9, 10, 11R17.5	\$20.00
9, 10R22.5	\$30.00
11R22.5, 24.5	\$55.00, \$60.00
12.00R24	\$50.00
12R22.5, 24.5	\$60.00
TUBELESS LOW PROFILE	
215, 235/75R17.5	\$15.00
225, 245, 265, 285/70R19.5	\$20.00
245, 265/75R22.5	\$15.00
255, 275/70R22.5	\$55.00
295/75R22.5	\$55.00
295/80R22.5	\$55.00
285/75R24.5	\$60.00
315/80R22.5	\$55.00
385, 425, 445/65R22.5	\$65.00
TUBE TYPE	
9.00R20	\$30.00
10.00R20	\$40.00
11.00R20	\$40.00
12.00R20	\$40.00

2 YEAR RADIAL CASING WARRANTY

Effective November 1, 2018, all Duraturn casings with a DOT manufactured date as of week 44 of 2018 will be warranted for workmanship and materials at 100% through the first and second retread for a period of six (6) years from the manufactured date indicated by the DOT number.

SAFETY WARNINGS

Serious injury or property damage may result from:

- TIRE FAILURE DUE TO UNDERINFLATION/ OVERLOADING. Follow the owner’s manual or tire placard in vehicle.
- TIRE FAILURE DUE TO EXCESSIVE HIGH SPEED. Follow the owner’s manual or tire placard in vehicle.
- EXPLOSION OF TIRE/RIM ASSEMBLY DUE TO IMPROPER MOUNTING. Only specially trained persons should mount tires.
- FAILURE TO MOUNT RADIAL TIRES ON APPROVED RIMS.
- FAILURE TO DEFLATE SINGLE OR DUAL ASSEMBLIES COMPLETELY BEFORE DISMOUNTING.
- TIRE SPINNING. On slippery surfaces such as snow, mud, ice, etc., do not spin tires in excess of 35 mph (55 kpm), as indicated on the speedometer. Personal injury and severe damage may result from excessive wheel spinning, including tire disintegration or axle failure.

