

REM-8



(MCS) HIGH-SPEED CRANE TIRE

The REM-8 high-speed crane OTR tire is U.S. DOT approved for on-highway use. The OEM Certified REM-8 is designed with a universal tread pattern to improve traction and deliver a more comfortable ride.

EXPLORE



| PRODUCT CODE | TIRE SIZE | PATTERN | LOAD SYMBOL | SPEED MAX (KM/H) | SPEED MAX (MPH) | OVERALL DIAMETER (IN) | SECTION WIDTH (IN) | TREAD DEPTH (32NDS) | RIM | SINGLE MAX LOAD/PRESSURE | WEIGHT | TYPE |
|--------------|-------------------------|---------|-------------|------------------|-----------------|-----------------------|--------------------|---------------------|-----------|--------------------------|-------------|------|
| 1117184241 | 14.00R24 (385/95R24) | REM-8 | ★★★ | 70 | 43 | 54 | 16 | 31 | 10.00W | 13948lb/144psi | 294lb/133kg | TL |
| 1117184251 | 14.00R25 (385/95R25) | REM-8 | ★★★ | 70 | 43 | 54 | 16 | 31 | 10.00/1.5 | 13948lb/144psi | 298lb/135kg | TL |
| 1117186251 | 16.00R25 (445/95R25) | REM-8 | ★★★ | 70 | 43 | 59 | 17 | 33 | 11.25/2.0 | 16280lb/130psi | 461lb/209kg | TL |
| 1117196251 | 16.00R25 (445/95R25) | REM-8 | ★★ | 80 | 50 | 59 | 17 | 33 | 11.25/2.0 | 14740lb/130psi | 448lb/203kg | TL |
| 1117190251 | 20.5R25 (525/80R25) | REM-8 | ★★ | 70 | 43 | 59 | 21 | 39 | 17.00/2.0 | 17065.4lb/101psi | 525lb/238kg | TL |
| 1117190252 | 525/80R25 (20.5R25) | REM-8 | ★★ | 80 | 50 | 59 | 21 | 39 | 17.00/2.0 | 15620lb/101psi | 525lb/238kg | TL |