

REM-2S



NEW
TIRE



(E2/L2/G2)
EARTHMOVER/LOADER/
GRADER

The REM-2S is an all-weather/mud and snow (M+S) radial OTR tire designed with a wide, non-directional tread pattern for increased traction and year-round performance, especially in snow and ice conditions. The tread siping allows for increased traction in severe and icy conditions, while the wide tread blocks are designed for a flatter footprint and longer tire life. These features make it an excellent choice in earthmover, loader and grader applications.

EXPLORE

PRODUCT CODE	TIRE SIZE	PATTERN	LOAD SYMBOL	SPEED MAX (KM/H)	SPEED MAX (MPH)	OVERALL DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX LOAD/ PRESSURE	WEIGHT	TYPE
1107174241	14.00R24 (385/95R24)	REM-2S	★★	50 10	30 5	54	16	30	10.00	12320lb/101psi 20900lb/115psi	298lb/135kg	TL
1107174251†	14.00R25 (385/95R25)	REM-2S	★★	80	50	53.5	15.5	30	10.00/1.5	13230lb/131psi	335lb/152kg	TL
1107177251	17.5R25	REM-2S	★★	50 10	30 5	53	18	36	14.00/1.5	11990lb/ 76psi 18700lb/94psi	353lb/160kg	TL
1107170251	20.5R25	REM-2S	★★	50 10	30 5	58	21	39	17.00/2.0	16060lb/76psi 25300lb/94psi	510lb/231kg	TL
1107173251	23.5R25	REM-2S	★★	50 10	30 5	64	24	43	19.50/2.5	20350lb/65psi 31900lb/83psi	708lb/321kg	TL

* Mud and Snow

† DOT approved