

# RR680



## OptiGreen Series

### PREMIUM REGIONAL/ ALL-POSITION STEER TIRE

- Micro sipes on the groove edges prevent the onset of irregular wear.
- Premium 5-rib tread design with wide shoulders provides for durability and even wear in regional steer/all position applications.
- SmartWay® California CARB compliant tread compounds for lower rolling resistance and better fuel economy.

**EXPLORE**



PRODUCT CODE	TIRE SIZE	PLY RATING	LOAD RANGE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAM. (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX LOAD/PRESSURE	DUAL MAX LOAD/PRESSURE	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT	TYPE
1133671255	11R22.5	14	G	144/142	L	41.4	11.1	18	8.25	6175lb/105psi	5840lb/105psi	19.8	499	114lb/51kg	TL
1133671256	11R22.5	16	H	148/145	L	41.4	11.1	18	8.25	6940lb/123psi	6390lb/123psi	19.8	499	119lb/54kg	TL
1133679255	295/75R22.5	14	G	144/141	M	40.6	11.7	18	9.00	6175lb/110psi	5675lb/110psi	19.5	504	118lb/54kg	TL
1133679257	295/75R22.5	16	H	146/143	M	40.6	11.7	18	9.00	6610lb/120psi	6005lb/120psi	18.9	518	121lb/55kg	TL
1133671455	11R24.5	14	G	146/143	L	43.3	10.9	18	8.25	6610lb/105psi	6005lb/105psi	20.8	476	128lb/58kg	TL
1133671456	11R24.5	16	H	149/146	L	43.3	10.9	18	8.25	7160lb/120psi	6610lb/120psi	20.8	476	60lb/133kg	TL
1133678455	285/75R24.5	14	G	144/141	L	41.5	11.0	18	8.25	6175lb/110psi	5675lb/110psi	19.5	492	123lb/55kg	TL
1133679214	9R22.5	14	G	136/134	L	38.3	9.1	18	6.75	4940lb/120psi	4675lb/120psi	17.9	206	111lb/50kg	TL
1133679256	295/80R22.5	16	H	150/147	M	41.3	11.9	18	9.00	7390lb/120psi	6780lb/120psi	19.8	491	120lb/54kg	TL
1133679258	295/80R22.5	18	J	152/149	M	41.3	11.9	18	9.00	7830lb/130psi	7160lb/130psi	19.8	491	120lb/54kg	TL
1133671258	315/80R22.5	20	L	157/154	L	42.4	12.2	18	9.00	9090lb/130psi	8270lb/130psi	19.9	488	142lb/64kg	TL
1133670457*	305/75R24.5	18	J	154/149	M	42.7	11.6	19	9.00	8270lb/123psi	7160lb/123psi	19.6	486	138lb/63kg	TL

\* Only available in Mexico



www.DoubleCoinTires.com