

# REM-2



## (E3/L3) EARTHMOVER/LOADER TIRE

The Double Coin REM-2 Off-The-Road radial features an aggressive self-cleaning tread design. Engineered to deliver a smooth ride and superior traction in all types of terrain, the REM-2 is an OEM Certified OTR with an advanced casing design that promotes retreadability.

**EXPLORE**



| PRODUCT CODE | TIRE SIZE | PATTERN | LOAD SYMBOL | SPEED MAX (KM/H) | SPEED MAX (MPH) | OVERALL DIAMETER (IN) | SECTION WIDTH (IN) | TREAD DEPTH (32NDS) | RIM       | SINGLE MAX LOAD/ PRESSURE      | WEIGHT        | TYPE |
|--------------|-----------|---------|-------------|------------------|-----------------|-----------------------|--------------------|---------------------|-----------|--------------------------------|---------------|------|
| 1107167251   | 17.5R25   | REM-2   | ★★          | 50<br>10         | 30<br>5         | 53                    | 18                 | 34                  | 14.00/1.5 | 11990lb/76psi<br>18700lb/94psi | 347lb/157kg   | TL   |
| 1107160251   | 20.5R25   | REM-2   | ★★          | 50<br>10         | 30<br>5         | 58                    | 21                 | 39                  | 17.00/2.0 | 16060lb/76psi<br>25300lb/94psi | 510lb/231kg   | TL   |
| 1107163251   | 23.5R25   | REM-2   | ★★          | 50<br>10         | 30<br>5         | 64                    | 24                 | 45                  | 19.50/2.5 | 20350lb/76psi<br>31900lb/94psi | 741lb/336kg   | TL   |
| 1107166252   | 26.5R25   | REM-2   | ★★          | 50<br>10         | 30<br>5         | 69                    | 27                 | 47                  | 22.00/3.0 | 25300lb/76psi<br>40700lb/94psi | 1021lb/463kg  | TL   |
| 1107162955   | 29.5R25   | REM-2   | ★★          | 50<br>10         | 30<br>5         | 73                    | 29                 | 50                  | 25.00/3.5 | 30800lb/76psi<br>49280lb/94psi | 1295lb/587kg  | TL   |
| 1107167565   | 750/65R25 | REM-2   | ★★          | 50<br>10         | 30<br>5         | 64                    | 30                 | 54                  | 24.00/3.0 | 23320lb/61psi<br>40700lb/90psi | 1015lb/460kg  | TL   |
| 1107167765   | 775/65R29 | REM-2   | ★★          | 50<br>10         | 30<br>5         | 68.9                  | 30.3               | 58                  | 24.00/3.5 | 26730lb/62psi<br>45320lb/94psi | 1048lb/475kg  | TL   |
| 1107168765   | 875/65R29 | REM-2   | ★★          | 50<br>10         | 30<br>5         | 73.8                  | 35                 | 60                  | 28.00/3.5 | 34100lb/62psi<br>56650lb/94psi | 1478lb/ 670kg | TL   |