REM-6

(IND) INDUSTRIAL LUG TIRE

The Double Coin REM-6 radial design delivers optimum performance and traction in industrial lug, crane and port applications. The REM-6 is engineered with special tread compounds to run cool, fight rapid wear and deliver remarkable stability.

EXPLORE

PRODUCT CODE	TIRE SIZE	PATTERN	LOAD SYMBOL	SPEED MAX (KM/H)	SPEED MAX (MPH)	OVERALL DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX LOAD/ PRESSURE	WEIGHT	TYPE
1106355086	5.00R8	REM-6	111A5	25	15	18	5	31	3.00D	2398lb/145psi	23lb/10kg	T&F
1106356096	6.00R9	REM-6	121A5	25	15	21	6	31	4.00E	3190lb/145psi	38lb/17kg	T&F
1106356505	6.50R10	REM-6	128A5	25	15	23	7	34	5.00	3968lb/145psi	45lb/20kg	T&F
1106357026	7.00R12	REM-6	136A5	25	15	26	7	35	5.00S	4928lb/145psi	60lb/27kg	T&F
1106353156	315/70R15	REM-6	165A5	25	15	33	12	45	8.00	11330lb/145psi	131lb/59kg	TL, T&F
1106357056	7.00R15	REM-6	143A5	25	15	29	8	35	5.50	5995lb/145psi	71lb/32kg	T&F
1106357556	7.50R15	REM-6	146A5	25	15	30	8	38	6.00	6600lb/145psi	82lb/37kg	T&F
1106358255	8.25R15	REM-6	153A5	25	15	33	9	40	6.50	8050lb/145psi	104lb/47kg	T&F
1106352275	225/75R15	REM-6	149A5	25	15	28	9	31	7.00	7150lb/145psi	71lb/32kg	T&F
1106352575	250/70R15	REM-6	153A5	25	15	29	10	33	7.00	8030lb/145psi	78lb/35kg	T&F
1106351006	10.00R20	REM-6	166A5	25	15	42	12	44	7.50	11660lb/145psi	192lb/87kg	T&F
1106351206	12.00R20	REM-6	176A5	25	15	45	13	52	8.50	19570lb/145psi	245lb/111kg	T&F
1106351246	12.00R24	REM-6	178A5	25	15	49	13	49	8.50	20670lb/145psi	278lb/126kg	T&F
1106354241	14.00R24	REM-6	193A5	25	15	56	15	81	10.00	27340lb/145psi	512lb/232kg	T&F
1106354242	14.00R24	REM-6	193A5	25	15	56	15	81	10.00	27340lb/145psi	512lb/232kg	TL
1106351825	18.00R25	REM-6	207A5	25	15	65	20	81	13.00/2.5	46480lb/145psi	915lb/415kg	TL