

FR610



OptiGreen Series

ULTRA PREMIUM FUEL EFFICIENT STEER-POSITION TIRE

- New OptiGreen compound delivers low rolling resistance and maximum fuel efficiency.
- Innovative siping and defense grooves for long even wear.
- Durable casing construction resists fatigue and delivers industry-leading lower total cost of ownership.
- Micro siping throughout the tread delivers improved traction and stability.

EXPLORE



PRODUCT CODE	TIRE SIZE	PLY RATING	LOAD RANGE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAM. (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX LOAD/PRESSURE	DUAL MAX LOAD/PRESSURE	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT	TYPE
1133781255	11R22.5	14	G	144/142	L	41.4	11.0	19.5	8.25	6175lb/105psi	5840lb/105psi	19.4	500	124lb/56kg	TL
1133781256	11R22.5	16	H	148/145	L	41.4	11.0	19.5	8.25	6940lb/123psi	6390lb/123psi	19.4	500	128lb/58kg	TL
1133789255	295/75R22.5	14	G	144/141	L	40.3	11.7	20	9.00	6175lb/110psi	5675lb/110psi	18.8	516	121lb/55kg	TL
1133789256	295/75R22.5	16	H	146/143	L	40.3	11.7	20	9.00	6610lb/120psi	6005lb/120psi	18.8	516	125lb/57kg	TL
1133781455	11R24.5	14	G	146/143	L	43.2	10.9	19.5	8.25	6610lb/105psi	6005lb/105psi	20.1	480	129lb/59kg	TL
1133781456	11R24.5	16	H	149/146	L	43.2	10.9	19.5	8.25	7160lb/120psi	6610lb/120psi	20.1	480	133lb/60kg	TL
1133788455	285/75R24.5	14	G	144/141	L	41.5	10.9	20	8.25	6175lb/110psi	5675lb/110psi	19.5	501	122lb/55kg	TL