RLB406

OptiGreen™ Series

CLOSED SHOULDER DRIVE-POSITION TIRE

- Sipes in the tread blocks help to grip the road surface, providing excellent traction and stability.
- Lug base design and groove bottom protectors aid in preventing debris from drilling into the casing.
- Full 28/32" tread depth provides exceptionally long wear across multiple applications.



NEW TIRE

PRODUCT CODE	TIRE SIZE	PLY RATING	LOAD RANGE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAM. (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX LOAD/ PRESSURE	DUAL MAX LOAD/ PRESSURE	STATIC LOAD RADIUS	WEIGHT	TYPE
1133461256	11R22.5	16	H	148/145	L	41.7	11.0	29	8.25	6940lbs/123psi	6390lbs/123psi	20.8	140lb/63.5kg	TL
1133461456	295/75R22.5	16	G	144/141	L	41.7	11.7	29	9.00	6175lbs/110psi	5675lbs/110psi	19.2	132lb/59.9kg	TL
1133469256	11R24.5	16	H	149/146	L	43.7	11.2	29	8.25	7160lbs/120psi	6610lbs/120psi	20.4	144lb/65.5kg	TL

* Only available in