RLB800

PREMIUM DEEP TREAD ON/ OFF HIGHWAY SEVERE SERVICE DRIVE-POSITION TIRE

- Advanced chip/cut and abrasion resistant compounds for increased mileage.
- Extra deep open shoulder design evacuates mud and soft soil, providing traction even in challenging environments.
- Durable casing construction.

EXPLORE

PRODUCT CODE	TIRE SIZE	PLY RATING	LOAD RANGE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAM. (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX LOAD/ PRESSURE	DUAL MAX LOAD/ PRESSURE	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT	TYPE
1133501026	10.00R20	16	H	146/143	G	41.9	10.7	29	7.50	6610lb/120psi	6005lb/120psi	19.7	489	141lb/64kg	TT
1133501027	10.00R20	18	J	149/146	G	41.9	10.7	29	7.50	7160lb/135psi	6610lb/135psi	19.7	489	131lb/59kg	TT
1133501256	11R22.5	16	H	148/145	G	41.9	10.9	29	8.25	6940lb/123psi	6390lb/123psi	19.5	491	133lb/60kg	TL
1133501258*	11R22.5	16	H	148/145	G	41.9	10.9	29	8.25	6940lb/123psi	6390lb/123psi	19.5	491	133lb/60kg	TL
1133501456	11R24.5	16	H	149/146	G	43.9	10.9	29	8.25	7160lb/120psi	6610lb/120psi	20.3	468	140lb/63kg	TL
1133501459*	11R24.5	16	H	149/146	G	43.9	10.9	29	8.25	7160lb/120psi	6610lb/120psi	20.3	468	140lb/63kg	TL
1133501458	11R24.5	16	H	149/146	G	43.9	10.9	29	8.25	7160lb/120psi	6610lb/120psi	21.0	468	140lb/63kg	TL
1133502258	12R22.5	18	J	152/149	K	43.6	11.9	32.5	9.00	7830lb/135psi	7160lb/135psi	20.4	423	161lb/73kg	TL
1133502257*	12R22.5	18	J	152/149	K	43.6	11.9	32.5	9.00	7830lb/135psi	7160lb/135psi	20.4	423	161lb/73kg	TL
1133502250	12.00R24	20	L	150/157	G	49.2	12.3	40.5	8.50	9920lb/130psi	9090lb/130psi	22.8	422	203lb/92kg	TT