

# RR99



## PREMIUM ON/OFF HIGHWAY MIXED SERVICE ALL-POSITION TIRE

- Strong all-position tread pattern designed for multiple on/off highway uses.
- Outside shoulder grooves with zigzag center grooves provide added traction in mud and soft soil.

**EXPLORE**



| PRODUCT CODE | TIRE SIZE   | PLY RATING | LOAD RANGE | LOAD INDEX | SPEED SYMBOL | OVERALL DIAM. (IN) | SECTION WIDTH (IN) | TREAD DEPTH (32NDS) | RIM  | SINGLE MAX LOAD/ PRESSURE | DUAL MAX LOAD/ PRESSURE | STATIC LOAD RADIUS | REVS PER MILE | WEIGHT     | TYPE |
|--------------|-------------|------------|------------|------------|--------------|--------------------|--------------------|---------------------|------|---------------------------|-------------------------|--------------------|---------------|------------|------|
| 1133437565   | 7.50R16     | 14         | G          | 122/118    | L            | 31.9               | 8.3                | 16                  | 6.00 | 3305lb/112psi             | 2910lb/112psi           | 14.7               | 656           | 59lb/27kg  | TT   |
| 1133991256   | 11R22.5     | 16         | H          | 148/145    | L            | 41.3               | 10.9               | 21.5                | 8.25 | 6940lb/123psi             | 6390lb/123psi           | 19.5               | 496           | 124lb/56kg | TL   |
| 1133991456   | 11R24.5     | 16         | H          | 149/146    | L            | 43.4               | 10.9               | 21.5                | 8.25 | 7160lb/120psi             | 6610lb/120psi           | 21                 | 484           | 131lb/59kg | TL   |
| 1133992256   | 12R22.5     | 16         | H          | 152/148    | L            | 42.7               | 11.8               | 21.5                | 9.00 | 7830lb/120psi             | 6940lb/120psi           | 20.1               | 516           | 135lb/61kg | TL   |
| 1133992258   | 12R22.5     | 18         | J          | 152/149    | L            | 42.7               | 11.8               | 21.5                | 9.00 | 7830lb/61psi              | 7160lb/61psi            | 20.1               | 516           | 135lb/61kg | TL   |
| 1133433227   | 13R22.5     | 18         | J          | 154/151    | M            | 43.9               | 12.2               | 21.5                | 9.75 | 8270lb/123psi             | 7610lb/123psi           | 20.7               | 465           | 164lb/74kg | TL   |
| 1133991257   | 315/80R22.5 | 18         | J          | 156/152    | L            | 42.7               | 12.4               | 19                  | 9.00 | 8820lb/120psi             | 7830lb/120psi           | 19.9               | 484           | 144lb/66kg | TL   |
| 1133991259   | 315/80R22.5 | 22         | M          | 160/157    | J/65MPH      | 42.7               | 12.4               | 19                  | 9.00 | 10000lb/130psi            | 9090lb/130psi           | 19.9               | 483           | 149lb/67kg | TL   |
| 1133439205   | 9.00R20     | 14         | G          | 141/139    | M            | 40.2               | 10.1               | 19                  | 7.00 | 5675lb/115psi             | 5355lb/115psi           | 18.9               | 510           | 111lb/50kg | TT   |