

# TR100



## ULTRA PREMIUM SHALLOW TREAD TRAILER-POSITION TIRE

- Tread design promotes even wear in free rolling/trailer axle positions.
- Center rib designed to eject stones, preserving casing integrity and promoting multiple retreads.
- 14/32" tread depth delivers long original mileage.

**EXPLORE**



| PRODUCT CODE | TIRE SIZE   | PLY RATING | LOAD RANGE | LOAD INDEX | SPEED SYMBOL | OVERALL DIAM. (IN) | SECTION WIDTH (IN) | TREAD DEPTH (32NDS) | RIM  | SINGLE MAX LOAD/PRESSURE | DUAL MAX LOAD/PRESSURE | STATIC LOAD RADIUS | REVS PER MILE | WEIGHT     | TYPE |
|--------------|-------------|------------|------------|------------|--------------|--------------------|--------------------|---------------------|------|--------------------------|------------------------|--------------------|---------------|------------|------|
| 1133381255   | 11R22.5     | 14         | G          | 144/142    | M            | 41.0               | 10.9               | 14                  | 8.25 | 6175lb/105psi            | 5840lb/105psi          | 19.5               | 500           | 113lb/51kg | TL   |
| 1133381256   | 11R22.5     | 16         | H          | 148/145    | M            | 41.0               | 10.9               | 14                  | 8.25 | 6940lb/123psi            | 6390lb/123psi          | 19.5               | 500           | 117lb/53kg | TL   |
| 1133389255   | 295/75R22.5 | 14         | G          | 144/141    | M            | 40.2               | 11.7               | 14                  | 9.00 | 6175lb/110psi            | 5675lb/110psi          | 18.9               | 510           | 114lb/51kg | TL   |
| 1133381455   | 11R24.5     | 14         | G          | 146/143    | L            | 42.9               | 10.9               | 14                  | 8.25 | 6610lb/105psi            | 6005lb/105psi          | 20.8               | 476           | 124lb/56kg | TL   |
| 1133381456   | 11R24.5     | 16         | H          | 149/146    | L            | 42.9               | 10.9               | 14                  | 8.25 | 7160lb/120psi            | 6610lb/120psi          | 20.8               | 476           | 126lb/57kg | TL   |
| 1133388455   | 285/75R24.5 | 14         | G          | 144/141    | L            | 41.1               | 11.0               | 14                  | 8.25 | 6175lb/110psi            | 5675lb/110psi          | 19.3               | 505           | 117lb/53kg | TL   |